

## CHAIN SAW

## • PNEUMATIC



### TECHNICAL DATA

Operating pressure 6 bar.

	Blade length	Blade length usable	Power	Air consumption	Sound level	Vibration level	Air connection	Weight (without chain and blade)
Type	cm	cm	kW	m <sup>3</sup> /min	db(A)	m/s <sup>2</sup>		kg
<b>5 1026 0010</b>	52	43	3.0	2.9	93.1	<2.5	R3/4"female	8.5
<b>5 1027 0010<sup>1)</sup></b>	52	43	3.0	2.9	93.1	<2.5	R3/4"female	8.5
<b>5 1028 0010<sup>2)</sup></b>	52	43	3.0	2.9	93.1	<2.5	R3/4"female	8.5
<b>5 1029 0010<sup>3)</sup></b>	52	43	3.0	2.9	93.1	<2.5	R3/4"female	9.5

<sup>1)</sup>for cutting plastic <sup>2)</sup>for underwater use <sup>3)</sup>for underground mining

# SPITZNAS

Maschinenfabrik GmbH, Fellerstraße 4, D-42555 Velbert, Germany  
 Tel.: +49-2052-605-0 Fax.: +49-2052-605-29  
 E-Mail: sales@spitznas.de <http://www.spitznas.com>

06/11 E