



# PALETT EXPANDER

TOOLS FOR THE SPECIALIST



+

# SABRE SAW

OUR SUITABLE ACCESSORIES

PNEUMATIC



# TECHNICAL DATA

## PALLET EXPANDER

The single acting pneumatic cylinder separates the top and bottom plate of a wooden pallet and allows to cut the nails with a sabre saw.



**PNEUMATIC**



**OPERATING PRESSURE** 4-8 Bar

ORDER NO.	Piston stroke mm	Holder spacing mm	Expanding power at					Air consumption l/Hub	Connection	Noise level LpA	Vibration level m/s <sup>2</sup>	Weight kg
			4 bar	5 bar	6 bar	7 bar	8 bar					
<b>7 2510 0010</b>	42.00	90.00	1.26	1.63	1.99	2.36	2.72	0.17	R 1/4" female	<70.0	<2.5	2.7
<b>7 2511 0010</b>	28.00	90.00	1.26	1.63	1.99	2.36	2.72	0.11	R 1/4" female	<70.0	<2.5	2.5
<b>7 2512 0010</b>	42.00/62.00	90.00	1.26	1.63	1.99	2.36	2.72	0.17	R 1/4" female	<70.0	<2.5	2.7

Subject to technical change.

Performance data at an operating pressure of 4-8 bar.

## SABRE SAW

Pneumatic sabre saw with increased cutting speed and quick release tool adapter.



**PNEUMATIC**



**OPERATING PRESSURE** 6 Bar

ORDER NO.	Power	Air consumption	Stroke	Number of strokes	Noise level	Vibration level	Weight
	kW	m <sup>3</sup> /min	mm	rpm	dB(A)	chipboard/wooden beam m/s <sup>2</sup>	
<b>5 1237 0010</b>	1.8	2.0	28	2,800	90	18.3/28.3	4.9

Subject to technical change.

Performance data at an operating pressure of 6 bar.

## CONSTRUCTION TOOLS PROGRAM

### NEEDLE SCALERS



### RIVETING AND CHIPPING HAMMERS



### SHEAR HAMMERS



### SAND RAMMERS



### MIXERS



### PALLET EXPANDERS

